



Cold Cranking Simulator Viscosity (CCS) Standards

Dynamic mPa.s (cP)

Product Code	-5°C	-10°C	-15°C	-20°C	-25°C	-30°C	-35°C
VIS-CCS-8	-	-	-	-	-	-	-
VIS-CCS-14	-	-	-	-	-	-	-
CL08	-	-	-	-	-	-	899.0
CL09	-	-	-	-	-	-	1082
CL10	-	-	-	-	-	868.8	1733
CL11	-	-	-	-	-	1419	2363
CL12	-	-	-	-	844.1	1627	3396
CL13	-	-	-	-	1707	2826	4895
CL14	-	-	-	829.3	1561	3144	6855
CL15	-	-	-	1625	2632	4460	7955
CL16	-	-	-	1346	2632	5550	12678
CL17	-	-	1354	2147	3540	6104	11114
CL19	-	-	938.0	1748	3487	7492	17560
CL20	-	-	1141	2141	4311	9414	22297
CL22	-	-	1321	2522	5170	11396	-
CL24	-	-	1493	2859	5867	13082	-
CL25	-	988.8	1807	3504	7311	16557	-
CL26	-	1206	2235	4389	9328	21524	-
CL28	-	1321	2504	5032	11030	-	-
CL30	-	2287	3648	6033	10448	19012	-
CL32	-	1792	3501	7286	16565	-	-
CL34	-	2555	4085	6794	11832	-	-
CL38	-	2901	5815	12660	-	-	-
CL42	-	5089	8370	14409	-	-	-
CL48	2362	4561	9527	21354	-	-	-
CL53	-	5922	9812	17002	-	-	-
CL60	3649	7204	15320	-	-	-	-
CL68	-	9597	-	-	-	-	-
CL74	6023	12702	-	-	-	-	-

All values stated are nominal - 08/12/2008